

Safety Signaling Relay Style EN1 - TECHNICAL DATA

PART NUMBER	CON- ACTS	RATED VOLTS d.c.	PIN CODE	COIL RES OHMS	MAX FULL OP.V. d.c.	MIN REL V d.c.	FULL REL	PLUGBOARD DRILLED TO	NO. OF CONN- ECTORS	REMARKS
E/R/01	12F 4B	24	001	345	19.2	3.6	2.0	ELB/130/1	34	BR-930A
E/R/02	8F 8B	24	002	345	19.2	3.6	2.0	ELB/130/2	34	BR-930A
E/R/03	8F 4B	24	001	345	19.2	3.6	2.0	ELB/130/1	26	BR-930A
E/R/04	6F 6B	24	002	345	19.2	3.6	2.0	ELB/130/2	26	BR-930A
E/R/05	4F 4B	24	002	345	19.2	3.6	2.0	ELB/130/2	18	BR-930A
E/R/06	12F 4B	50	003	1350	40.0	7.5	4.0	ELB/130/3	36	BR-930A
E/R/07	8F 8B	50	004	1350	40.0	7.5	4.0	ELB/130/4	36	BR-930A
E/R/08	8F 4B	50	003	1350	40.0	7.5	4.0	ELB/130/3	26	BR-930A
E/R/09	6F 6B	50	004	1350	40.0	7.5	4.0	ELB/130/4	26	BR-930A
E/R/10	4F 4B	50	004	1350	40.0	7.5	4.0	ELB/130/4	18	BR-930A