

Safety Signaling Relay Style EBA - TECHNICAL DATA

PART NUMBER	CON-ACTS	RATED VOLTS d.c.	PIN CODE	COIL RES OHMS	MAX FULL OP.V. d.c.	MIN REL V d.c.	FULL REL	PLUGBOARD DRILLED TO	NO. OF CONN-ECTORS	REMARKS
E/L/R/01	12F 4B	24	025	215	19.2	3.6	2.0	ELB/130/25	34	BR-932A
E/L/R/02	8F 4B	24	025	215	19.2	3.6	2.0	ELB/130/25	26	BR-932A
E/L/R/03	8F 8B	24	026	215	19.2	3.6	2.0	ELB/130/26	34	BR-932A
E/L/R/04	6F 6B	24	026	215	19.2	3.6	2.0	ELB/130/26	26	BR-932A
E/L/R/05	4F 4B	24	026	215	19.2	3.6	2.0	ELB/130/26	18	BR-932A
E/L/R/06	12F 4B	50	027	720	40.0	7.5	4.0	ELB/130/27	34	BR-932A
E/L/R/07	8F 4B	50	027	720	40.0	7.5	4.0	ELB/130/27	26	BR-932A
E/L/R/08	8F 8B	50	028	720	40.0	7.5	4.0	ELB/130/28	34	BR-932A
E/L/R/09	6F 6B	50	028	720	40.0	7.5	4.0	ELB/130/28	26	BR-932A
E/L/R/10	4F 4B	50	028	720	40.0	7.5	4.0	ELB/130/28	18	BR-932A