

Safety Signaling Relay Style EL

Description:

A Miniature tractive Armature DC magnetically Latched Neutral Line Relay, plug-in-type for Railway Signaling purpose.

General Data:

- Nominal rated voltage: 50V & 24V DC.
- Standard Contact Arrangement: 11F/4B, 8F/6B.
- Contact rating: Continuous 3 Amps
- Weight: 1.7 kgs. (approx.)
- Environmental Characteristics: exceeds BS 2011
- Excellent Vibration / Shock characteristics



Features

- Safety signaling relay conforming to BR Standard giving high level of reliability over 1 million in service.
- Fine Silver to Silver Impregnated Graphite safety contact prevent welding.
- Armature Torque provided by gravity and Helical Spring maintaining front contact gap when relay de-energized.
- Moulded relay base, which interlocks with its respective Plugboard.

Safety Signaling Relay Style EL - TECHNICAL DATA Ordering Particulars

[Click To view](index.php/safety-signaling-relay-style-el-technical-data/?tmpl=component)(index.php/safety-signaling-relay-style-el-technical-data/?tmpl=component)

RELAYS (Please specify the following details when ordering) :

- Rated Voltage
- Contact Arrangement
- PIN Code

PLUGBOARD AND ANCILLARY PARTS

- Plug board drill No.
- No. of Connectors
- Relay fixing clip