

Safety Signaling Relay Style ENA1 - TECHNICAL DATA

PART NUMBER	CON- ACTS	RATED VOLTS d.c.	PIN CODE	COIL RES OHMS	MAX FULL OP.V. d.c.	MIN REL V d.c.	FULL REL	PLUGBOARD DRILLED TO	NO. OF CONN- ECTORS	REMARKS
E/A/R/01	12F 4B	24	021	215	19.2	3.6	2.0	ELB/130/21	34	BR-931A
E/A/R/02	8F 8B	24	022	215	19.2	3.6	2.0	ELB/130/22	34	BR-931A
E/A/R/03	8F 4B	24	021	215	19.2	3.6	2.0	ELB/130/22	26	BR-931A
E/A/R/04	6F 6B	24	022	215	19.2	3.6	2.0	ELB/130/22	26	BR-931A
E/A/R/05	4F 4B	24	022	215	19.2	3.6	2.0	ELB/130/22	18	BR-931A
E/A/R/06	12F 4B	50	023	720	40.0	7.5	4.0	ELB/130/23	34	BR-931A
E/A/R/07	8F 8B	50	024	720	40.0	7.5	4.0	ELB/130/23	34	BR-931A
E/A/R/08	8F 4B	50	023	720	40.0	7.5	4.0	ELB/130/23	26	BR-931A
E/A/R/09	6F 6B	50	024	720	40.0	7.5	4.0	ELB/130/24	26	BR-931A
E/A/R/10	4F 4B	50	024	720	40.0	7.5	4.0	ELB/130/24	18	BR-930A