

## Safety Signaling Relay Style ET9

### Description:

A Miniature Tractive Armature DC Neutral Track Relay plug-in-type for Railway Signalling purpose. **General Data:**

- Nominal rated voltage: 1.4 V DC.
- Standard Contact Arrangement: 2F, 2F/2B (also other contact arrangements available).
- Contact rating: Continuous 3 Amps.
- Weight: 1.7 kgs. (approx).
- Environmental Characteristics: exceeds BS 2011.
- Excellent Vibration / Shock characteristics.



### Features

- Safety signaling relay conforming to BR Standard giving high level of reliability over 1 million in service.
- Fine Silver to Silver Impregnated Graphite safety contact prevent welding.
- Fine Silver moving contact riveted and soldered on to Phosphor Bronze Spring to ensure good electrical connection.

- Armature Torque provided by gravity and Helical Spring maintaining front contact gap when relay de- energized.
- Moulded relay base, which interlocks with its respective Plugboard.

### **Safety Signaling Relay Style ET9 - TECHNICAL DATA**

[Click To View](index.php/safety-signaling-relay-style-et9-technical-data/?tmpl=component)(index.php/safety-signaling-relay-style-et9-technical-data/?tmpl=component)

Ordering Particulars Please specify the following details when ordering :

#### **RELAYS**

- Rated Voltage
- Contact Arrangement
- PIN Code

#### **PLUGBOARD AND ANCILLARY PARTS**

- Plug board drill No.
- No. of Connectors
- Relay fixing clip