

## Safety Signaling Relay Style EUCX1

### Description:

A Miniature tractive armature AC Lamp Proving relay designed for Position Light function indications. **General Data:**

- Nominal rated voltage: 1.4 Amp AC.
- Standard Contact Arrangement: 2F/2B, 3F/3B.
- Contact rating: Continuous 3 Amps.
- Weight: 1.7 kgs. (approx).
- Environmental Characteristics: exceeds BS 2011.
- Excellent Vibration / Shock characteristics.



### Features

- Safety signaling relay conforming to BR Standard giving high level of reliability over 1 million in service.
- Fine Silver to Silver Impregnated Graphite safety contact prevent welding.
- Fine Silver moving contact riveted and soldered on to Phosphor Bronze Spring to ensure good electrical connection.
- Armature Torque provided by gravity and Helical Spring maintaining front contact gap when relay de-energized.
- Moulded relay base, which interlocks with its respective Plugboard.

## **Safety Signaling Relay Style EUCX1 - TECHNICAL DATA**

Click To View

**RELAYS** (Ordering Particulars Please specify the following details when ordering) :

- Rated Voltage
- Contact Arrangement
- PIN Code

**PLUGBOARD AND ANCILLARY PARTS**

- Plug board drill No.
- No. of Connectors
- Relay fixing clip